



ORACLE LED
S Y S T E M S

LINKS

Modular Rental Solutions

3.9, 4.8, 5.9, 6.9



IN/OUT



GREEN



2000
REFRESH RATE



LIGHT
WEIGHT



RUGGED



MODULAR



CONVEX
CONCAVE

EXCLUSIVE U.S. DISTRIBUTOR OF

LIGHTLINK™

ORACLELEDSYSTEMS.COM

10537 Glenoaks Boulevard, Pacoima, California 91331
323-451-1533

COPYRIGHT © 2015, ORACLE LED SYSTEMS, INC. ALL RIGHTS RESERVED. PATENTS PENDING WORLDWIDE. THE ORACLE LED LOGO, BLACK WIDOW™, ARE TRADEMARKS OF ORACLE LED SYSTEMS, INC. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



Powered by
Macroblock
THE GOLD STANDARD



ORACLE LED
S Y S T E M S

LINKS

Modular Rental Solutions

The Links Rental Series are inventive, uniquely functional, highly cost-effective panels and feature a tailor-made user experience, combining both convenience and quality creative applications for the rental market

Parameters

Indoor

Pixel pitch(mm)	3.91	4.81	5.95	6.9
Pixel configuration	SMD2121 3-in-1	SMD2121 3-in-1	SMD3528 3-in-1	SMD3528 3-in-1
Pixel Per Module(Pixels/m ²)	63,536	43,264	28,224	20,736
Module Size(mm)	250x250	250x250	250x250	250x250
Brightness(cd/m ²)	1600≥≥1200	1600≥≥1200	≥1500 (2500)	≥1500
High IC Chip	MBI 5151	MBI 5151	MBI 5151	MBI 5151
Viewing Angle(H/V)	H: 140/V:140	H: 140/V:140	H: 140/V:140	H: 140/V:140
Cabinet Size(mm x mm)	500x500x65	500x500x65 / 500X1000X65	500x500x65 / 500X1000X65	500x500x65 / 500x1000x65
Cabinet Weight	16lbs	16lbs / 30lbs	16lbs / 30lbs	16lbs / 30lbs
Display Refresh Rate (Hz)	≥3800	≥3000	≥3000	≥3000
Driving Method	1/16	1/13	1/11(1/7)	1/9
Curvable	N/A	N/A	Yes	Yes
Input voltage(nominal)(V)	AC 110,220,110-220	AC 110,220,110-220	AC 110,220,110-220	AC 110,220,110-220
Input Power (Max)(W/m ²)	≈400	≈400	≈400 (800)	≈400
Input Power (Avg.)(W/m ²)	≈200	≈200	≈200 (400)	≈200
Lifespan (H)	≥100,000	≥100,000	≥100,000	≥100,000



Parameters

Outdoor

Pixel pitch(mm)	4.81	5.95	6.944
Pixel configuration	SMD2727(Black LED)	3-in-1 SMD 3528(Black LED)	3-in-1 SMD 3528
Pixel Per Module(Pixels/m ²)	43,263	28,235	20,738
Module Size(mm)	250x250	250x250	250x250
Brightness(cd/m ²)	≥5500	≥5500	≥5500
High IC Chip	5151	5151	5151
Viewing Angle(H/V)	H: 140/V:140	H: 140/V:140	H: 140/V:140
Cabinet Size(mm x mm)	500x500x65 / 500X1000X65	500x500x65 / 500X1000X65	500x500x65 / 500X1000X65
Cabinet Weight	16lbs / 30lbs	16lbs / 30lbs	16lbs / 30lbs
Display Refresh Rate (Hz)	≥2000	≥2000	≥2000
Driving Method	1/13	1/11(1/7)	1/9
Curvable	N/A	Yes	Yes
Input voltage(nominal)(V)	AC 110,220,110-220	AC 110,220,110-220	AC 110,220,110-220
Input Power (Max)(W/m ²)	≈400	≈400 (800)	≈400
Input Power (Avg.)(W/m ²)	≈200	≈200 (400)	≈200
Lifespan (H)	≥100,000	≥100,000	≥100,000



EXCLUSIVE U.S DISTRIBUTOR OF

LIGHTLINK
TECHNOLOGY

ORACLELEDSYSTEMS.COM

Powered by
Macroblock
THE GOLD STANDARD